

## SCALEOVIEW L19W-9

### 19 Inch LCD widescreen Display

Issue April 2008

Pages 2

An attractive price doesn't mean that you have to compromise on style or performance. The SCALEOVIEW L19W-9 widescreen display offers best performance for the home office and multimedia, such as photo editing and gaming. With its extremely slim and stylish design, the SCALEOVIEW L19W-9 fits perfectly into your home environment.

#### Highlights

- 19-inch widescreen display for a perfect viewing experience
- Best performance to an affordable price
- Stylish black design with a silver front
- Very easy and comfortable to use
  - Plug & Play
  - Auto-adjust
  - Easy-to-use OSD menu

#### Ergonomics

- Optimum flicker-free and distortion-free picture
- Excellent colour purity
- Well balanced brightness uniformity
- Excellent high contrast up to (1000:1)
- Space saving design

#### Technical highlights

- 19" (48.1cm) LCD widescreen display
- Excellent contrast up to 1000:1
- Brightness 300 cd/m<sup>2</sup>
- Fast response time (typ.) 5 ms
- Internal power supply

#### Reliability

- Low power consumption
- Power management according to EPA
- Guaranteed quality and stability



<b>Visible screen diagonal</b>	19 inch (48.1 cm)
<b>Resolutions</b>	
Pixels	1440 x 900
Pixels*	1280 x 768
* expanded	
<b>Picture size</b>	408 x 255 mm
<b>Colours</b>	16.2 million
<b>Pixel Pitch</b>	0.2835 mm
<b>Frequencies</b>	
Horizontal	31 - 81 kHz
Vertical	56 - 75 Hz
<b>Brightness (typical)</b>	300 cd/m²
<b>Contrast up to</b>	1000:1
<b>Viewing angle (cr &gt;=5)</b>	
Horizontal	170°
Vertical	170°
<b>Response time (typical)</b>	5 ms
<b>Plug and Play</b>	VESA DDC2B
<b>Setting options</b>	
Brightness (Back light control)	
Contrast, Volume control	
Picture position (horizontal and vertical), H-size, Phase,	
Color temperature and individual color setting	
Auto-adjust (direct access key)	
Activate factory settings	
Menu language	
<b>OSD Language</b>	
English, German, Spanish, French, Italian, Russian,	
Swedish, Dutch	
<b>Base</b>	
Tilt angle	-5°/ +20°
<b>Audio characteristics</b>	
Audio signal input	3.5mm stereo phone jack
Audio output	1 W (L) + 1 W (R)

<b>Electrical values</b> (internal power supply)	
Rated voltage	100 - 240 V
Frequency	50 - 60 Hz
Power draw	
EPA 'On Mode'	19 W
Max.	<50 W
EPA 'Off Mode'	0.7 W
Protection class	1
<b>Temperatures/ dimensions/ weight</b>	
Ambient temperature (to IEC721):	
Working (recommended)	5°C to 35°C
Storage	-20°C to 60°C
Dimensions (H x W x D):	
(with stand)	359.3 x 442.2 x 206 mm
Weight (Monitor only)	4.4 kg
<b>Reliability</b>	
MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight	50,000 h
(brightness > 50 % of original brightness)	
<b>Compliance with standards</b>	
Product safety	EN60950
Ergonomics	GS mark
	ISO13406-2
	(Pixel fault class II)
Radiation immunity and	CE certification according
RFI suppression	to EC Directive
	2004/108/EEC
	(EN55022/B, EN55024
	EN61000-3-2/-3);
	TCO'03
<b>Video input</b>	1 x D-SUB
<b>Accessories</b>	
Power cable (1.5 m)*	For wall socket
	(Euro-Schuko-Type CEE7)
Data cable (1.5 m)*	D-SUB (15-pin)
Audio cable (1.8 m)*	3.5mm stereo phone jack
* detachable on display	
<b>Special features</b>	
	Standardized mounting
	interface according
	VESA FPMPI (100 mm)
	Kensington Lock
<b>Order code</b>	S26361-K1223-V204
<b>EAN</b>	4333643525002